



NOTE:

1. THE SITE DEVELOPER SHALL LEAVE THE CLEANOUT RISER 3'-4' ABOVE GRADE AND IT SHALL REMAIN SO UNTIL LOT BUILD OUT. THE RISER SHALL THEN BE CUT AND CAPPED AT FINISHED GRADE WITH A CONCRETE PAD.
2. ALL CLEANOUTS AND CONCRETE PADS TO BE FLUSH WITH FINISH GRADE.
3. UTILITY CONTRACTOR TO INSTALL & PRESSURE TEST WYE AND INSTALL CLEANOUT RISER. INSTALL CLEANOUT AND CONCRETE PAD AT LOT BUILDOUT.
4. ETCH CURB WITH "S" WHERE LATERAL CROSSES UNDER CURB
5. ALL COMMERCIAL AND RESIDENTIAL SINGLE LATERALS SHALL HAVE 6" CLEANOUTS.
6. MAINTAIN A MINIMUM OF 3' CLEARANCE FREE OF ALL PLANTINGS & STRUCTURES AROUND CLEANOUT.
7. CLEANOUT CAPS SHALL BE SLOTTED OR HAVE A RECESSED NUT.

**SANITARY CLEANOUT DETAIL**

TWA-06  
2009